



KOYUNCU TICARET LIMITED SIRKETI

Address: Rihtim Cad. No:28 Derya Is Merkezi
Kat:5 No:78 Kadikoy 34716 Istanbul - Turkey

Phone: + 90(216)449 4205/06

Fax: + 90(216)449 4260

Web: <http://www.gasequipments.com>

Email: info@gasequipments.com

TECHNICAL SPECIFICATIONS :

CHASSIS :

MAIN BODY I CAST. MAIN BODY CONNECTIONS U CAST HIGH STRENGTH S16252 SHEET METAL.

LAMA : CEMTAŞ S16252 CHASSIS OUTER DIAMETER : 1400mm

AXLES : SEYMAK OR KOC BRAND 300.000 KMS TRAVEL WITHOUT MAINTENANCE. 2 EACH STATIONARY. 1 EACH WITH LIFTING MECHANISM. EACH WITH 9 TONS CAPACITY, THEY ARE PRODUCED WITH S16052 QUALITY 14mm SHEET METAL WITH RECTANGULAR FITTINGS CENTER FITTED 10 EACH WHEEL NUT INNER FRAME. ESKAN RODS ARE BEDDED WITH G40 ROLLERBEARINGS THE FRAME ROLLERBEARINGS ARE 33213 OUTER, 218248 INNER SKF GERMAN ROLLERBEARINGS. THE FRAMES ARE EQUIPPED WITH COOLING SYSTEM AND WITH SUPERMAN BRAKE LININGS.

SUSPENSION SYSTEM: AIR BEDS WITH 813 STANDART CONTITEC BRAND AND TOGETHER WITH LEVEL VALVES.

BRAKES : WABCO OR HALDEX BRAND. AUTOMATIC WITH LOAD LEVEL VALVE. 2 EACH WABCO BRAND LOAD LEVELING VALVE 2 EACH ARFESAN 30X24 WITH ALARM, 4 EACH ARFESAN BRAND 24 BRAKE BELLOWS

AIR SUPPLY: AIR SUSPENSION : PROVIDES AIR FOR THE LIFTING OF FRONT AXLE, BRAKE CIRCUIT, AND ABS. 2 EACH AIR LINE FILTERS, 2 EACH AIR TANK. IN THIS SYSTEM POLYAMID BRAKE PIPES AND SPECIAL FITTINGS ARE UTILIZED

FRONT LIFTING AXLE : OPERATED FROM THE DRIVERS CABIN

RATCHETS : SELF ADJUSTABLE AYS BRAND AND AUTOMATIC.

SHOCK ABSORBERS : SHOCK ABSORBERS ARE UTILIZED DISABLING THE EXCESS MOVEMENT OF THE AXLES.

PARK LEGS : JOST TYPE. DOUBLE CIRCUIT 25 TON CAPACITY TELESCOPIC AND MECHANICAL SYSTEM.

KING PIN : JOST TYPE. SAE STANDARDS. 2" DIAMETER KZ 101 2 H 50 X PRODUCED OF CAST STEEL. (42Cr Mo4) - DURABLE FOR HIGH TENSION AND BREAKS. EASY HANDLING FOR ASSEMBLY AND DISASSEMBLY BY MENAS OF BOLTED CONNECTIONS.

ELECTRICAL CONNECTIONS : EBC STANDARDS. 24 V ILLUMINATION SYSTEM 7 FUNCTIONS SABO BRAND LAMPS, 7 PINNED ELECTRICAL SOCKETS (24N/24S), 6 EACH SIDE LAMPS (AND 1 EACH ABS SOCKET

TIRES AND WHEEL RIMS : LASSA OR BRIDGESTONE BRAND 38.5 / 65 R 22.5 DIMENSIONS. 6 EACH WHEEL RIMS. JANTSA BRAND 11.75 X 22.5 DIMENSIONS.

FENDERS : HALF FENDERS WITH SUITABILITY TO REGULATE AND WITH ESTHETIC VIEW AND OFFERING SOLUTION TO MUD SPILLS.

REAR BUMFERS : SDD BRAND PANEL BUMFERS

PAINT : THE SURFACES ARE CLEANED AND COATING WITH EPOXY WITH HIGH STRENGTH FOR CORROSION IS APPLIED.

ATTACHMENTS :

1 EACH	FOOD CASINGS
1 EACH	50 LT WATER TANK
1 EACH	SINGLE SPARE TIRE HOLD
2 EACH	FILLING ADAPTOR
2 EACH	SPHERICAL VALVE
1 EACH	DIRT HOLDERS
1 EACH	MONOMETER WITH GLYSERYN
1 EACH	THERMOMETER WITH GLYSERYN
2 EACH	SECURITY VALVE
1 EACH	HYDRAULIC OPERATOR

TOOL KITS : AXLE, WHEEL NUT AND PORYAKEP WRENCHES

TANKER SPECIFICATIONS :

MAIN BODY : 10mm DIN EN 10028 Part2 1993 STANDARD ERDEMIR P355 GH SHEET METAL
OPERATING PRESSURE : 17.5 ATU
TEST PRESSURE : 26.5 ATU
OPERATING TEMPERATURE : min -10 C max -50 C
WAVEBREAKER : 2 EACH

NOTE THE DIMENSIONS ARE AS ATTACHED DIAGRAM

SERVICE : 24 HOURS OF SERVICE LOCALLY WITHIN TURKEY

DELIVERY PERIOD : 60 DAYS AFTER RECEIVING FIRM ORDER (+/- 5 WOKING DAYS)

TERMS OF WARRANTY : THE LPG TANK IS UNDER THE PRODUCERS WARRANTY FOR A PERIOD OF 1 YEAR AGAINST ANY MANUFACTURING AND CONTRUCTION FAULTS. THIS IS VALID AS OF THE DELIVERY OF THE TANKS. THE TOTAL WARRANTY PERIOD AFTER DELIVERY AND THE INVOICE DATE CANNOT EXCEED 1.5 YEARS. THE PRODUCER IS NOT RESPONSIBLE AND DOES NOT ACCEPTS ANY FAILURES OF THE TANK DUE TO WRONG AND FSLA HANDLING OF THE UNITS. THE COMPANY PROVIDES A PERIOD OF FIVE YEARS WITH PAYMENT OF MAINTENANCE AND SPARE PARTS SUPPORT.

THE EXCEPTIONS TO THE WARRANTY SCOPE :

BRAKE LININGS AND OIL MAINTENANCE
SUSPENSION AIR BAGS AND Z AXES
ELECTRICAL WARE
ANY OTHER TIRES THEN LASSA & BRIDGESTONE

NOTE : TIRES ARE UNDER WARRANTY BY THE PRODUCER COMPANY FOR 1 YEAR 100.000 KMS

CONDITIONS :

THE TECHNICAL SPECIFICATIONS ARE VALID FOR THE ATTACHED TANK DRAWINGS
ANY OTHER CONDITIONS NOT MENTIONED HEREIN ARE NOT IN WARRANTY SCOPE OF THE PRODUCERS.